ECLIPSE BIFOLD Model TYPE 1L



ENTRANCE



CHARACTERISTICS

CAB DOOR TYPE: AUTO BIFOLD DOORS
ENTRANCE DOOR TYPE: SWING DOORS
BIFOLD DOORS FINISH: PAINT OR STAINLESS STEEL
FULLY AUTOMATIC OPERATION TO OPEN THE DOORS UPON ARRIVAL AT THE LANDING
LIGHTWEIGHT ALUMINUM SILL
FOR CAB LONGER THAN 54", EXTENSION PANELS
WILL BE PROVIDED AT THE ENDS OF EACH WALLS



CLEAR INSIDE CAB WIDTH		CLEAR INSIDE CAB LENGTH		A FINISHED RUNWAY WIDTH		B FINISHED RUNWAY LENGTH		C RAIL CENTER LINE		D DOOR CENTER LINE	
mm	Inches	mm		mm	Inches	mm	Inches	mm	Inches	mm	Inches
1016	40	1219	48	1410	55 1/2	1422	56	762	30	845	33 1/4
1016	40	1372	54	1410	55 1/2	1575	62	838	33	845	33 1/4
1016	40	1524	60	1410	55 1/2	1727	68	914	36	845	33 1/4

DOCUMENT REVISION 000, DATE: 01/25/17



MOUNTING BRACKET
4 WALL ANCHOR POINTS MIN. PER BRACKET
2 PER SIDE OF RAIL BRACKET CENTER LINE
PULL OUT FORCE PER FASTENER 69 kg [152 LBS]

CANNOT HAVE HABITABLE SPACE BELOW PIT

FINAL RAIL BRACKET RB3	BELOW THE MOTOR CONSULT YOUR CONCORD REPRESENTATIVE FOR EXACT LOCATION
INTERMEDIATE RAIL BRACKET RB2	32"[813mm] INTERVALS AFTER 2nd BOTTOM BRACKET
BOTTOM RAIL BRACKET RB1	39" [991mm] & 71" [1804MM] ABOVE PIT FLOOR

RAIL FORCES



*R1	*R2
138.2 kg [304 lbf]	88.2 kg [194 lbf]

RAIL ASSY WEIGHT: 24.5 kg / m [18.0 lbs / ft]

PIT FORCE: R3

PIT FLOOR TO SUPPORT LOAD OF(INCLUDES IMPACT)
2909 kg [6400 lbs]

ENTRANCE SIDE LEGEND



RESIDENTIAL ELEVATOR
ECLIPSE BIFOLD TYPE 1L-40" WIDTH

ALL INFORMATION IS SUBJECT TO CHANGE.
PLEASE REFERENCE OUR ON-LINE DRAWINGS AT
www.savaria.com FOR THE MOST RECENT UPDATES

THE INFORMATION DISCLOSED HEREIN IS THE EXCLUSIVE PROPERTY OF savaria AND MAY NOT BE USED BY OTHERS WITHOUT PRIOR WRITTEN CONSENT

SHEET# 1/1